



### **PARAFUSO ALLEN COM CABEÇA MÉTRICO DIN 912 AÇO**

**REFERÊNCIA: 095-**

<b>A</b>	<b>3</b>	<b>4</b>	<b>5</b>	<b>6</b>	<b>8</b>	<b>10</b>	<b>12</b>	<b>14</b>	<b>16</b>	<b>18</b>	<b>20</b>	<b>22</b>	<b>24</b>	<b>27</b>	<b>30</b>	<b>36</b>
<b>B</b>	<b>0,50</b>	<b>0,70</b>	<b>0,80</b>	<b>1,00</b>	<b>1,25</b>	<b>1,50</b>	<b>1,75</b>	<b>2,00</b>	<b>2,00</b>	<b>2,50</b>	<b>2,50</b>	<b>2,50</b>	<b>3,00</b>	<b>3,00</b>	<b>3,50</b>	<b>4,00</b>
<b>C</b>	<b>2,50</b>	<b>3,00</b>	<b>4,00</b>	<b>5,00</b>	<b>6,00</b>	<b>8,00</b>	<b>10,00</b>	<b>12,00</b>	<b>14,00</b>	<b>14,00</b>	<b>17,00</b>	<b>17,00</b>	<b>19,00</b>	<b>19,00</b>	<b>22,00</b>	<b>27,00</b>
<b>D</b>	<b>3,00</b>	<b>4,00</b>	<b>5,00</b>	<b>6,00</b>	<b>8,00</b>	<b>10,00</b>	<b>12,00</b>	<b>14,00</b>	<b>16,00</b>	<b>18,00</b>	<b>20,00</b>	<b>22,00</b>	<b>24,00</b>	<b>27,00</b>	<b>30,00</b>	<b>36,00</b>
<b>E</b>	<b>5,50</b>	<b>7,00</b>	<b>8,50</b>	<b>10,00</b>	<b>13,00</b>	<b>16,00</b>	<b>18,00</b>	<b>21,00</b>	<b>24,00</b>	<b>27,00</b>	<b>30,00</b>	<b>33,00</b>	<b>36,00</b>	<b>40,00</b>	<b>45,00</b>	<b>54,00</b>
<b>F</b>	<b>18,00</b>	<b>20,00</b>	<b>22,00</b>	<b>24,00</b>	<b>28,00</b>	<b>32,00</b>	<b>36,00</b>	<b>40,00</b>	<b>44,00</b>	<b>48,00</b>	<b>52,00</b>	<b>56,00</b>	<b>60,00</b>	<b>66,00</b>	<b>72,00</b>	<b>84,00</b>

**A= DIÂMETRO DO PARAFUSO**

**B= ROSCA**

**C= CHAVE**

**D= ALTURA DA CABEÇA**

**E= DIÂMETRO DA CABEÇA**

**F= ALTURA DA ROSCA**

**\*Diâmetros aproximados**

**\*Material Aço alto carbono 12.9**

**\*Tratamento superficial oxidado oleado**

**\*Norma DIN 912 ISO 4762 Rosca grossa métrica**

**\*Medidas em milímetros**

**\*\*Altura da rosca pode variar, consultar**